

## 335W Q.PEAK DUO BLKL-G6+ All-Black Solar Module by Hanwha



Price: CAD \$359.00

**SKU:** HWQPEAKDUO\_BLKL-G6-335

**Product Categories:** [Discontinued](#)

**Product Tags:** [335w](#), [335w solar panel](#), [60 Cell](#), [black](#), [hanwha g6](#), [hanwha q.cells](#), [canada](#), [q.cells 335](#), [Q.PEAK DUO BLKL-G6+](#), [Q.PEAK DUO BLKL-G6+ canada](#), [Qcells 335w](#)

**Product Page:**

<https://www.modernoutpost.com/product/335w-q-peak-duo-blkl%e2%80%90g6-all-black-solar-module-by-hanwha/>

### Product Summary

The 335W Q.PEAK DUO BLKL-G6+ All-Black Solar Module by Hanwha is one of our most specified solar modules for residential systems. Value, performance, and good looks. All from a company that consistently ranks at the top of the 3rd party ethics

& reliability scorecards.

## Product Description

The 335W Q.PEAK DUO BLKL-G6+ All-Black Solar Module by Hanwha is one of our most specified solar modules for residential systems. Value, performance, and good looks. All from a company that consistently ranks at the top of the 3rd party ethics & reliability scorecards.

### Q.ANTUM TECHNOLOGY: LOW LEVELIZED COST OF ELECTRICITY

Higher yield per surface area, lower BOS costs, higher power classes, and an efficiency rate of up to 19.5 %.

### INNOVATIVE ALL-WEATHER TECHNOLOGY

Optimal yields, whatever the weather with excellent low-light and temperature behavior.

### ENDURING HIGH PERFORMANCE

Long-term yield security with Anti LID and Anti PID Technology, Hot-Spot Protect and Traceable Quality Tra.Q™.

### EXTREME WEATHER RATING

High-tech aluminum alloy frame, certified for high snow (5400 Pa) and wind loads (4000 Pa).

### A RELIABLE INVESTMENT

Inclusive 25-year product warranty and 25-year linear performance warranty.

### STATE OF THE ART MODULE TECHNOLOGY

Q.ANTUM DUO combines cutting edge cell separation and innovative wiring with Q.ANTUM Technology.

### Q.PEAK DUO BLKL-G6+ Specifications

Power at MPP : 335

Short Circuit Current (Isc) : 10.47A

Open Circuit Voltage (Voc) : 40.41V

Current at MPP (Impp) : 9.97A

Voltage at MPP Vmpp : 33.62V

Efficiency :  $\geq 18.7$   
Cell Format : 6 × 20 monocrystalline (half-cut)  
Dimensions : 1740x1030x32mm (68.5x40.6x1.26) Weight : 19.9 kg (43.9 lbs)  
**Download the Data Sheet**

Product Attributes

- Dimensions: 1 &times; 1 &times; 1 cm
- Weight: 20 kg

Product Gallery

