

MNEPV2 : 2A, 150VDC Din Rail Mount Breaker



Price: CAD \$24.99

SKU: MNEPV2

Product Categories: [Fuses & Breakers](#), [Supply](#), [Wiring & BOS](#)

Product Tags: [150vdc](#), [2a](#), [breaker](#), [canada](#), [dc](#), [dc breaker](#), [din rail](#), [midnite](#), [midnite solar](#), [mnepv](#), [mnepv2](#), [solar](#)

Product Page: <https://www.modernoutpost.com/product/mnepv2-2a-150vdc-din-rail-mount-breaker/>

Product Summary

The Midnite Solar MNEPV2 is a 2A, 150VDC din rail mount breaker (13mm wide).

Product Description

The Midnite Solar MNEPV2 is a 2A, 150VDC din rail mount breaker (13mm wide).

Note: Branch circuit rated 489A

MidNite's breakers are rated to break the full rated load at the rated voltage repeatedly, with NO DAMAGE. Always use a properly sized breaker for disconnecting.

- Environmental Rating - Type 1 (Indoor) - DC Voltage Rating - 150VDC - Wire Size Range - 14 to 6 AWG - Width - .51 in (13mm) - Number of poles - 1 - 10,000 AIC

MNEPV2 breakers are the same as CBI QY breakers except the standard used is inadequate for the solar industry.

MidNite breakers have been evaluated by ETL to 150VDC and are listed for US and Canada. All of the NRTL listings still apply. Breakers ordered under the CBI part numbering system will not be listed for 150VDC and in many cases are not suitable for the solar industry.

All MidNite circuit breakers can be used at 100% rated current when mounted in a MidNite enclosure. Breaker Torque Value: 20 In-Lbs (2.3NM).

Listed for US & Canada

Product Attributes

- Dimensions: N/A

Product data have been exported from - Modern Outpost
Export date: Sat Jul 4 12:51:39 2020 / +0000 GMT

- Weight: .3 kg