

Samlex EVO-2224 : 2200 Watt Pure Sine Inverter/Charger



Price: CAD \$2,999.00

SKU: SXEVO2224

Product Categories: [Off-Grid : Inverter/Chargers <3kW](#), [Inverters](#), [Inverters : >3kW](#), [Off-Grid : Inverter/Chargers](#), [Mod Sine](#), [Shop](#)

Product Tags: [2200 Watt](#), [2200w](#), [24V](#), [canada](#), [charger](#), [evo-2212](#), [evo-2224](#), [inverter](#), [Pure Sine](#), [samlex](#), [Samlex EVO-2212](#), [Samlex EVO-2224](#), [sinewave](#), [transfer switch](#)

Product Page:

<https://www.modernoutpost.com/product/samlex-evo-2224-2200-watt-pure-sine-inverter-charger/>

Product Summary

The EVO-2224 is part of the Samlex Evolution series of inverter/chargers. Ideal for cabins, RV's, boats, and service vehicles, the Evolution series combines Pure Sinewave inverter with advanced battery charger and transfer switch, all in one unit! This is the 24V edition.

The EVO-2224 : 2,200 Watts, 70A charger, 40A transfer switch

Product Description

EVOLUTION Series Inverter/Charger : EVO-2224 2,200 Watt Pure Sinewave inverter, 24VDC input, 70A charger, 40A transfer switch

The Samlex EVO-2224 is part of the Samlex Evolution series of inverter/chargers. Ideal for cabins, RV's, boats, service vehicles, as well as alternative energy, back-up and emergency power applications. The Evolution series combines Pure Sinewave inverter with advanced battery charger and transfer switch, all in one unit!

Using state-of-the-art technology, the Samlex EVO inverter/charger operates at 165 million instructions per second with lightning fast load & response times, has 9 points of physical protection monitoring (being scanned up to 10,000 times per second) to detect fault conditions & protect itself in a vast range of adverse environments.

The EVO-2224 is a 2200 Watt Pure Sine inverter, 24 VDC input, 120 VAC output, 50/60 Hz. It intelligently integrates a 70 Amp 4 stage Battery Charger and a 40 Amp Transfer Relay into an advanced and affordable off-grid power solution.

(EVO-RC remote control sold separately. See page for EVO-RC for product details.

Samlex EVO-2224 Design Features...

AC Inputs

Two separate AC inputs - one for grid (priority #1), one for generator (priority #2), connect simultaneously, no need to reconfigure when different power sources are available.

Generator Input is specifically designed to have more tolerance for wave form distortion, prevents unnecessary "rejection of AC input and switch to inverter" by tolerating distorted wave forms that can be produced by gritty generators

Each AC input is programmable for voltage and frequency. User determines what the min and max thresholds are to switch from Grid or Generator to Inverter.

Generator start can be initiated by "Status Relay" contact, can be programmed to activate when grid is lost.

Solar Input

Connect a solar charge controller directly to the EVO through the Battery Charger

external DC Input, seamlessly integrates solar charging into the EVO's power system.

ONLINE Mode can be used to prioritize Batteries/Inverter over the grid, ideal for those wishing to operate primarily on solar power (when the grid is available, but might be costly).

Battery Charger

3 or 4 stage charging with Equalization (must be manually initiated).

Adaptive algorithm is used during Bulk to assess the condition of the battery. Subsequent stages are then based on the condition of the battery rather than pre-set time periods for Absorption and Float. Prevents unnecessary charging, extends the life of batteries.

Programmable - set battery voltage thresholds to initiate charging.

Transfer Switch

Zero transfer time when switching from Inverter to Grid. When grid comes on, the inverter synchronizes with the wave form and then transfers instantly at zero crossing.

<16ms transfer when going from Grid to Inverter. When grid is lost, the transfer relay switches to inverter at the correct place in the wave form, the transfer takes less than 16ms.

Surge Capacity (Power Boost)

The EVO has 3X surge power

Additionally, the EVO has large power overload allowances available for long periods of time. Increased inverter capacity means you can size your inverter smaller to handle heavy surge loads, reducing costs.

State-of-the-Art Technology

The EVO operates at 165 million instructions per second producing lightning fast load and response times

The EVO is practically indestructible. It has "Bullet-Proof Intelligence" in the form of 9 physical points of protection monitoring being scanned up to 10,000 times per second for adverse conditions. The EVO will detect fault conditions and initiate a healthy shutdown before any product damage can be done.

The EVO-RC remote control (sold separately) can be used to capture detailed EVO performance data. Records all detected faults and the conditions leading up to them. Data is stored on a removable 16GB SD Card (in the remote). Use data to analyze trends for more efficient use of system resources

The EVO uses five temperature sensors placed throughout the unit to determine operation of 2 speed controlled cooling fans. Reduces unnecessary fan noise and energy consumption by only running when and where the fans are needed.

Samlex EVO-2224 Specifications...

- Input : 24 VDC - Output : 120 VAC - Watts : 2200 Watts - Surge : 6600 Watts -
- Outlets : Hard Wired - Fuse : External - Remote Control : EVO-RC (Optional Remote Control) - Safety : ETL safety listed to stringent UL standards: 1741, 458, and to CSA C22.2 No. 107.1-01. EMI/EMC compliant with FCC Part 15(B), Class B and RoHS Compliant. - Warranty : 2 Year Limited - Weight : 27kg / 59 lbs - Dimensions : 32.5 x 42.6 x 20.7 cm / 12.79 x 16.77 x 8.15 in

Samlex EVO-2224 Documentation...

[Spec Sheet](#)

[User Manual](#)

Product Attributes

- Dimensions: N/A
- Weight: 29 kg

Product Gallery

