
# SC-10 SunCharger 10W Solar Trickle Charger



Price: CAD \$169.00

SKU: SXSC-10

Product Categories: Boats & Yachts, Home, Off-Grid: 32 & 36-Cell (12V Nominal),

On The Road, On The Water, Projects: Crystalline, RV & Van Systems, Solar

Modules, Supply

Product Tags: 10w, canada, charger, samlex, sc-10, solar, solar panel, suncharger

, SunCharger 10, trickle charger

### **Product Page:**

https://www.modernoutpost.com/product/sc-10-suncharger-10w-solar-trickle-charge r/

## **Product Summary**

The SC-10 SunCharger is perfect for maintaining the 12V battery in your RV, car, boat, motorcycle, snowmobile, SeaDoo, or ATV with power from the sun. Ultra slim, compact, & weatherproof, with NO metal to rust or glass to break. A great idea for

boats & vehicles in winter storage. Use the SunCharger 10 for maintaining larger vehicle batteries.

### **Product Description**

The SC-10 SunCharger is perfect for maintaining the 12V battery in your RV, car, boat, motorcycle, snowmobile, SeaDoo, or ATV with power from the sun. Ultra slim, compact, & weatherproof, with NO metal to rust or glass to break. A great idea for boats & vehicles in winter storage. Use the SunCharger 10 for maintaining larger vehicle batteries.

Plug the SunCharger 10 into any connected 12V lighter (CLA) socket to begin trickle charging your battery.

SC-10 SunCharger 10W Features...

- Trickle charge any 12V battery - Maintenance-free - Environmentally friendly - Integrated blocking diodes to prevent discharge from the battery - Comes with 3m (10') weather resistant cable - 2-Year Warranty

### SC-10 Specifications...

- Type of cells: Poly-crystalline - No. of cells in series in one string: 36 - Nominal Rated Power: 9.5W - Output Voltage (Open Circuit), Voc 21.5 VDC - Output Voltage (At Maximum Power Point): Vmp 17.0V - Output Current (Short Circuit): Isc 0.60A - Output Current (At Maximum Power Point): Imp 0.56 A - Connecting cable: 3 M, AWG #18, weather-resistant - Standard cigarette plug with replaceable 10 A fuse type AGC-10 - Operating Temperature -35°F to +175°F (-37°C to + 79°C) - Dimensions (LxWxH) 30.4 x 38.1 x 1.35cm (12 x 15 x 0.53) - Weight: 0.9 Kg (2 lbs)

#### **Product Attributes**

- Dimensions: 1 × 1 × 1 cm

- Weight: 1.9 kg