

Switch 10 Core Solar Recharging Kit by Goal Zero



Price: CAD \$169.00

SKU: GZCORE10-KIT

Product Categories: [Discontinued](#)

Product Tags: [canada](#), [charger](#), [core 10 kit](#), [goal zero](#), [goal zero switch](#), [goal zero switch 10 core](#), [goal zero switch 10 core canada](#), [solar](#), [switch 10](#), [switch 10 core](#), [usb](#), [USB solar charger](#)

Product Page:

<https://www.modernoutpost.com/product/switch-10-core-solar-recharging-kit-by-goal-zero/>

Product Summary

The Switch 10 Core Solar Recharging Kit by Goal Zero. It's equal parts phone charger, flashlight, and fan, the Switch 10 Core Multi-Tool is an all-in-one power solution for your pack. Quick charge phones, POV cameras, and other USB-powered

gear, then switch on a flashlight for bright light anywhere, or a fan to cool off. Solar-ready with included Nomad 7 Plus for rugged, reliable power wherever you go.

Product Description

The Switch 10 Core Solar Recharging Kit by Goal Zero. It's equal parts phone charger, flashlight, and fan, the Switch 10 Core Multi-Tool is an all-in-one power solution for your pack. Quick charge phones, POV cameras, and other USB-powered gear, then switch on a flashlight for bright light anywhere, or a fan to cool off. Solar-ready with included Nomad 7 Plus for rugged, reliable power wherever you go.

Goal Zero Switch 10 Core Kit Features & Specifications

CHARGE TIMES

Nomad 7 Plus Solar Panel: 2.5 - 5 hours

USB Source: 4 Hours

PORTS

USB port (output): 5V, up to 1.5A (7.5W max), regulated

USB port (input): 5V, up to 1A (5W max)

SOLAR

Rated Power: 7W

Open Circuit Voltage: 8-9V

Cell Type: Monocrystalline

BATTERY DETAILS

Cell Chemistry: Li-ion NMC

Cell Type: 18650 by LG chem/Samsung

Cell Capacity: 11.1Wh (3.7V, 3000mAh)

Lifecycles: hundreds of cycles

Shelf-life: Keep plugged in, or charge every 3-6 months

Fuses: none

Management system: Charging and low-battery protection built-in

GENERAL

Product SKU: 42034

Includes: USB Fan, USB Flashlight Head

Chainable: No

Weight: 4 oz (113 g)

Dimensions: 4.5 x 1 x 1 in (11.4 x 2.5 x 2.5 cm)

Operating usage temp.: 32-140 F (0-40 C)

Certs: CE, FCC, ROHS

Warranty 12 months

Product Attributes

- Dimensions: 1 × 1 × 1 cm
- Weight: .9 kg

Product Gallery



