

Switch 10 Multi-Tool Solar Kit by Goal Zero



Price: CAD \$99.00

SKU: GZCORE10-KIT-1

Product Categories: [Discontinued](#)

Product Tags: [canada](#), [charger](#), [core 10 kit](#), [goal zero](#), [goal zero switch](#), [goal zero switch 10 core](#), [goal zero switch 10 core canada](#), [solar](#), [switch 10](#), [switch 10 canada](#), [switch 10 core](#), [usb](#), [USB solar charger](#)

Product Page:

<https://www.modernoutpost.com/product/switch-10-multi-tool-solar-kit-by-goal-zero/>

Product Summary

More than a phone charger, more than a flashlight; the only all-in-one power solution for your pack. Quick charge phones, POV cameras, and other USB-powered gear, then switch on a flashlight for bright light anywhere, or a fan to cool off. It's

solar-ready and features a replacement, rechargeable battery that powers up from any USB.

Product Description

More than a phone charger, more than a flashlight; the only all-in-one power solution for your pack. Quick charge phones, POV cameras, and other USB-powered gear, then switch on a flashlight for bright light anywhere, or a fan to cool off. It's solar-ready and features a replacement, rechargeable battery that powers up from any USB.

This kit differs from the [Switch 10 Core Kit](#)] which features the Nomad 7+ solar panel

Goal Zero Switch 10 Kit Features & Specifications

CHARGE TIMES

Nomad 7 Solar Panel: 4-6 hours

USB Source: 4 Hours

PORTS

USB port (output): 5V, up to 1.5A (7.5W max), regulated

USB port (input): 5V, up to 1A (5W max)

SOLAR

Rated Power: 7W

Open Circuit Voltage: 8-9V

Cell Type: Monocrystalline

BATTERY DETAILS

Cell Chemistry: Li-ion NMC

Cell Type: 18650 by LG chem/Samsung

Cell Capacity: 11.1Wh (3.7V, 3000mAh)

Lifecycles: hundreds of cycles

Shelf-life: Keep plugged in, or charge every 3-6 months

Fuses: none

Management system: Charging and low-battery protection built-in

GENERAL

Product SKU: 21013

Includes: Solar panel, Battery, USB Fan, USB Flashlight Head

Chainable: No

Weight: 4 oz (113 g)

Dimensions: 4.5 x 1 x 1 in (11.4 x 2.5 x 2.5 cm)

Operating usage temp.: 32-140 F (0-40 C)

Certs: CE, FCC, ROHS

Warranty 12 months

Product Attributes

- Dimensions: 1 × 1 × 1 cm
- Weight: .9 kg

Product Gallery



